



- A) Lift Height: **180" - 15'**
- B) Clearance: **136" - 11'4"**
- C) Bucket Roll Back Angle: **40°**  
Bucket Dump Angle: **47°**
- D) Reach at Max Height: **9"**
- E) Reach at Ground Level: **16"**

	2800 PSI	3000 PSI
<b>Lift Capacity - AWC*</b> <small>(31.5" forward from pin)</small>	4700	5035
<b>Lift Capacity - Pivot Pin</b>	7460	7990

\*AWC - Actual Working Capacity

## PACKAGE COMPONENTS

- Freedom-Mount™
- Remote Control Coupler
- Snap-Attach™
- Hose Kit
- Standard Bracket Set
- Heavy Duty Grill Guard
- Hydra-Snap™ Manifold
- Bucket Level Indicator & Height Indicator
- 98" Large Capacity Bucket with Bolt-On Blade
- Plug-n-Play Lineless Hydraulics
- Smart-Pac Cylinders
- Rotational Height & Level Indicators

## LOADER SPECIFIC ATTACHMENTS

### Loader Upgrades

- 108" Large Capacity Bucket
- 3rd Steel Line with MTD Couplers
- Level Up Advantage
- Comfort Ride

### Attachments - Hay Handling

- 2-Prong Bale Spear
- 3-Prong Bale Spear
- 4-Prong Bale Spear
- Stack Saver I & II
- Bale Handler
- Bale Grab
- Squeezer™

### Attachments - Material Handling

- Z-47 Feeder Bucket
- Feed Bunk Bucket
- Tine Bucket
- Fork Bucket
- Brush Crusher™
- Brush Crusher™ Finishing Teeth
- Cat Claw 3-D Grab Fork
- Sabertooth for Tine Bucket
- 42" Fork Lift
- 48" Fork Lift
- Extendable Boom

### Additional Attachments

- 84"-96" Dozer Blade
- 96" V-Plow
- 96"-120" Snow Scraper
- Snap-Attach™ Adapters - Set (2)
- Snap-Attach™ Synchronizer



**WESTENDORF MANUFACTURING CO. INC.**

P.O. BOX 29 • ONAWA, IA 51040 • PH: (712) 423-2762 • FAX: (712) 423-1460  
Email: sales@westendorfmfg.com Website: www.loaders.com